evolutionary Technology or Powerful Adhesion on 3-D Parts is

0000

00

POLYDYNE" PRO



Intelligent, Powerful, Reliable Corona System



PolyDyne Pro™ – 3DT's powerful and versatile corona treatment system is designed to improve wettability on materials resistant to printing, adhesive and coating processes. Easily integrates into high-speed printing, extrusion and coating lines.

PolyDyne Pro has been thoroughly upgraded to include the latest in electrical engineering. It features precise, smart operation and feedback. It is adaptable to numerous applications such as 3-D plastic parts, plastic sheets, tubing, foam and more.

Treating Thick Materials IS Possible

3DT's approach to corona treatment goes beyond 3-dimensional parts. Our advanced designs are capable of treating thick materials such as corrugated plastic boards and foam stock. In the past these materials have presented numerous challanges. Now, 3DT makes it possible to treat these materials in a high-preformanceand efficent manner.

PolyDyne Pro's High-Performance Components:

- Compact, state-of-the-art generator and high-voltage transformer(s)
- Color touchscreen monitors all system parameters such as output level, treatment mode, fault log
- · Sophisticated remote interface
- · Downloadable USB operation log
- Custom features: Custom-designed treating station, electrode assembly, ozone filtration, automation and product handling.











3DT

For Maximum Flexibility and Performance

MultiDyne™ utilizes corona discharge to uniformly and consistently increase surface tension on 3-D parts. MultiDyne's technology creates powerful bonding for printing, coating and adhesion applications and is especially suited for polymer parts. Simple and complex 3-dimensional shapes are treatable with the flexibility of the MultiDyne system.

MultiDyne can be incorporated into existing or new production lines or as a stand-alone workstation. Each system is furnished as a complete set of standard components, including a generator with high-voltage transformer(s), air supply system, treating head(s), including control panel and fault monitoring system. MultiDyne is available with single or multiple treating heads, depending on your application.

MultiDyne Advantages:

- MultiDyne is available with 1 to 4 treating heads.
 Custom systems with more treating heads are available.
- Corona treatment is delivered to unlimited lengths of material in widths up to 2.5 inches (65mm) per head.
- The generator supplies power to high-voltage transformer(s) which then directly supplies the treating head(s), resulting in low-frequency corona discharge.
- Capable of treating surfaces adjacent to metal inserts or areas held in a metal fixture














3DT's Commitment to Innovation:

As part of our dedication to continual improvement and innovation, three of our systems have been thoroughly re-engineered. The new Pro series includes: optimized control panels and software, a newly developed generator producing more powerful discharge at precise levels, modular replacement parts, and more. At last, the most challenging applications are possible.



Flexibility in Corona Treatment

FlexiDyne Pro[™] is a self-contained corona treating system designed to treat 3-dimensional plastic parts. The FlexiDyne Pro system substantially raises surface energy and thereby improves bonding on polymer parts. It is ideal for the treatment of labware, eye lenses, headlight housings, container lids and numerous other applications. Any non-metallic item (up to 12" wide by 1.5" high) can receive uniform corona treatment of all exposed areas without set-up changes. FlexiDyne Pro can be operated as a stand-alone workstation or integrated production lines.

FlexiDyne Pro Advantages:

- Improves adhesion for printing, painting, coating, and adhesive applications
- Alters surface chemistry for improved adhesion of cell and tissue culture growth
- Recipe-based menu operation provides consistent results
- Treats different sizes and shapes without set up changes
- Automatic part detection signals treatment only when parts are in the treating chamber
- System monitoring and fault detection ensure uniform treatment results


The New FlexiDyne Pro

FlexiDyne has been an important system in 3DT's product line for years. But, changing technology has led to several improvements: a redesigned generator capable of producing a larger corona field, higher surface treatment levels, faster production and the ability to treat larger parts.


Note how the dyne solution adheres to the corona treated surface on the petri dish to the left, while the solution beads up and resists the untreated surface on the right.













Surface Treatment of Catheter Tubing

The TubeDyne™ corona treating system is designed to improve adhesion on the outside treatment of tube ends.

Any tubing up to ¼ inch (6mm) in diameter, with or without metal inserts, can be placed in the holding fixture and receive uniform corona treatment at a length of approximately 2.00 inches (50mm).

TubeDyne is a compact, self-contained tabletop corona treating system including integrated generator, transformer, electrode assembly, holding fixture and ozone filter.

The system is PLC-controlled and features an operator console with a human machine interface (HMI), including monochrome display screen with status menu, run time log, service hour log and alarm/troubleshooting screen.






TubeDyne Advantages:

- Improves surface tension on Pebax, PP, PE, nylon and more
- Self-contained compact tabletop system
- Enhances bonding of housing to catheter tube ends
- Powerful, repeatable and uniform treatment
- Treats up to ¼ inch (6mm) in diameter without set-up changes
- Please inquire about our system capable of treating tube diameter beyond ¼ inch (6mm)





Advanced Technology

3DT, a leader in 3-dimensional treating systems, takes corona treating a giant leap into the future. 3DT's broad program of corona treating systems gives you the ability to treat virtually any 3-dimensional polymer surface regardless of shape, with superior quality results.

ASMA DYNE PRO







Versatile, Effective Surface Treating

PlasmaDyne ProTM utilizes atmospheric plasma technology to effectivel and uniformly treat surfaces for the improved adhesion of glue, paint, ink, flocking, coatings, and laminates. Plasma technology raises surface energy for powerful bonding.

Plasma surface treatment (also called in-air or atmospheric plasma) modifies the molecular structure of many difficult-to-bond materials without causing harm to the surface. PlasamDyne Pro's process improves the surface tension on polymers, rubber, metal, glass, ceramic, paperboard and composites and is adaptable to countless applications.


PlasmaDyne Pro is Ideal for:

- · Automotive rubber seals
- · Medical parts and packaging
- Automotive headlight housings
- · Solar panels and glass
- · Silicon rubber window seals
- · Glue lines on cartons

Plasma Micro Cleans Surfaces

PlasmaDyne Pro micro cleans glass, metal and polymer surfaces by removing impurities, contaminants, residue, and organic compounds. This process, also referred to as etching, provides another important aspect in improving adhesion and enhances surfaces for secondary processes.

PlasmaDyne Pro is customized for your application including options in treating width from 3/8" to 1 1/2". Multiple head systems are built to provide wider treatment areas.



Made In the USA

All equipment from 3DT is designed, fabricated, and manufactured 100% in-house in Germantown,



Wisconsin,

USA.



*PLASMA DYNE ** Ovne Pro

The New PlasmaDyne Pro

3DT's hardworking, classic plasma treatment system, PlasmaDyne, has been thoroughly updated as a part of the company's effort toward continual improvement. Updates include the newest in electrical engineering, components and design. Renamed PlasmaDyne Pro, the upgraded system features an optimized, sophisticated control panel, adjustable plasma treatment levels, energy efficiency, modular replacement parts, it's compact and economical.

PlasmaDyne Pro: powerful, smart, dependable and safe Advantages:

- · Customizable with up to 16 independently controlled treating heads
- · Self-contained floor model integrates into new or existing lines
- · Durable, all-metal treating heads and long-lasting electrodes
- Treating widths from 3/8" 1 ½" (10mm 40mm)
- Remote I/O interface that can be incorporated into the customer's PLC control system
- Color touch display- monitors all system parameters, includes troubleshooting and fault log
- · For use on conductive and non-conductive surfaces
- · Safe; produces no ozone and eliminates the risk of high-voltage shocks







Superior Bonding

PlasmaDyne radically improves adhesion by raising the surface tension on substrates, thereby ensuring consistent, repeatable bonding results.



Superior, Versatile Surface Treatment Solutions

3DT manufactures a complete line of highly rellable, innovative corona and plasma surface treatment systems. Our systems improve adhesion on a wide array of plastics, composites, cardboard, rubber, foam, glass, and metal.

3DT's systems create powerful bonding for printing, painting, coating, laminating and adhesion applications. Our technology is uniquely designed for treating molded and extruded 3-dimensional parts, as well as numerous other applications requiring improved surface energy and a long-lasting bond.

3DT is a leader in the surface treatment industry because only 3DT provides continual technological advancement, truly custom design, exceptional customer service, and reliable, long-lived systems made in the USA.

3DT is your single-source for process application design, manufacture, product handling, installation and service. With more than 25 years of experience we offer the most advanced, adaptable and dependable systems worldwide.

Learn more on our website at www.3DTLLC.com and contact us today! For a list of 3DT sales agents please visit our website.

3DI The Power To Adhere.

3DT LLC • N114 W18850 Clinton Drive • Germantown WI 53022 • USA Tel 262-253-6700 • Tel 888-3-CORONA • Fax 262-253-6977 Email: sales@3DTLLC.com • www.3DTLLC.com



